



SPREADER GREENSPIRIT II MS

Technical information

| | |
|------------------------------|--------------------------|
| DIMENSIONS | L.912 x l.250 x h.222 mm |
| SPREADING DISTANCE | 610 mm |
| SPREADING FORCE | 44 - 857 kN |
| MAX PULLING FORCE | 68 kN |
| MAX SQUEEZING FORCE | 149 kN |
| TRACTION WIDTH | 465 mm |
| WEIGHT (WITH BATTERY) | 18,1 kg |
| NOMINAL PRESSURE | 700 bar |
| CLASS EN 13204 | AS44/ 610-18,1 |

Characteristics

ROBUSTNESS and SAFETY

- Reinforced composite casing
- Removable waterproof cover for a complete protection of the battery
- Strong arms equipped with carbides tips and rumble strips for an optimal grip
- 4 LED lights to illuminate the cutting area
- Control handle far away from the On/Off switch for an optimal security

ERGONOMIC and AUTONOMOUS

- Compact, light and balance
- Compatible with M18 battery (or via an adapter with the M28, as well as with other commercially available batteries upon request)
- Same battery on all tools
- Battery available at all Milwaukee dealer

EASE OF USE

- Intuitive ON/OFF switch with built in light
- Unsymmetrical control handle for an easier recognition of the cutting direction
- Easy and quick battery insertion and replacement

MADE IN FRANCE

COMPATIBLE WITH M18 & M28 BATTERIES



Accessories

- Battery Li-ion 18V, 8Ah
- 220V Charger
- Power supply
- Transport bag
- M18 to M28 Scorpe Technologies battery adapter
- Set of chains



Option

- Waterproof cover



Sales service :
+33 (0)3 24 73 00 08

After Sales :
sav@scorpe.eu
+33 (0)3 24 73 00 02