

Aquafast
Le hameau de la sucrerie
5 route de Laon
08190 Saint-Germainmont
France

SKIMMER 3,5 HP

Technical informations

MINIMAL DEPTH OF WATER NEEDED	100 mm
WATER INTAKE WIDTH BETWEEN 2 ARMS	285 mm
MAX SKIM HEIGHT	2.5 m
MAX HEIGHT UNLOADING	12 m
TANK CAPACITY	0.85 L
MOTOR	Briggs & Stratton 3,5 HP 4 strokes
AUTONOMY (ON LOAD)	40 min
MAXIMUM FLOW	600 L / min
DISCHARGE OUTLET	2,5" DSPM (Coupling on demand)
WEIGHT	27 kg

The motor pump can run dry without time limit

Characteristics

- Easily stowable thanks to the removable and detachable float,
- Starting phase which does not require water and can therefore start dry,
- Robust and low-maintenance pump,
- Self-adjusting weir whatever the flow rate of the pump.
- Hatch underneath, it provides a water supplement to the motor pump, allowing for rinsing or standard water draw.

Options

- Additional pipe float
- Transport kit



Light, robust, efficient

Sales service :
+33 (0)3 24 73 00 08

After Sales :
sav@scorpe.eu
+33 (0)3 24 73 00 02