Fire Floating Pump 13 HP



Technical Information

Maximum flow rate: 1500 L/min – 0.1 bar Maximum pressure: 5.6 bar Pressure at 500 L/min: 3.45 bar Reservoir: 2.8 L Weight: 50 kg Remote control range: Up to 150m Pump autonomy time: 60 minutes at full charge Autonomy of each battery: Approximately 50 starts Charging time for each battery: 100 minutes Hose outlet diameter: DN65 Engine brand: Bridge and Straton, 13HP Pump dimensions: 750x750x550mm



After Sales sav@scorpe.eu +33 (0)3 24 73 00 02

Sales service +33 (0)3 24 73 00 08

www.scorpe.net

As part of the improvement of its products, Scorpe reserves the right to modify the specifications without prior notice. Non-contractual photo.



Advantages

Remote control:

- Start, Stop, Starter
- Slow mode, Fast mode

MANUAL START IN CASE OF BATTERY FAILURE

- Low fuel level alert: Indicated by a flashing red light
- Battery: Milwaukee M18 (5 or 8 Ah)
- Self-priming: Less than 2 seconds for self-priming
- Minimum water height: 4 cm

Possible pumping of contaminated water Capable of pumping water containing suspended particles



After Sales sav@scorpe.eu +33 (0)3 24 73 00 02

Sales service +33 (0)3 24 73 00 08

www.scorpe.net

As part of the improvement of its products, Scorpe reserves the right to modify the specifications without prior notice. Non-contractual photo.