

Road Rescue Scorp'Air S



Technical Information

| Model | 1,3T | 4T | 8T | 13T | 18T | 24T | 30T L | 30T | 38T | 54T | 65T | 81T |
|--------------------------------|---------|---------|---------|---------|---------|---------|----------|---------|---------|---------|---------|---------|
| Size (mm) | 150x150 | 200x200 | 300x300 | 380x380 | 420x420 | 510x510 | 1000x320 | 560x560 | 620x620 | 750x750 | 840x840 | 920x920 |
| Thick (mm) | 22 | 22 | 22 | 22 | 22 | 22 | 22 | 22 | 22 | 22 | 22 | 22 |
| Weight (kg) | 0.7 | 1.3 | 2.2 | 3.4 | 4.1 | 6 | 7.5 | 4 | 8.5 | 12.5 | 16.5 | 19.5 |
| Race (mm) | 90 | 115 | 175 | 220 | 245 | 295 | 215 | 320 | 345 | 410 | 465 | 515 |
| Lifting capacity at 10 bar (T) | 1.3 | 4 | 8 | 13 | 18 | 24 | 30 | 30 | 38 | 54 | 65 | 81 |
| Air volume at 10 bar (L) | 5.4 | 9 | 54 | 99 | 117 | 225 | 324 | 252 | 414 | 720 | 1044 | 1449 |
| Max inflation pressure | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 |

Advantages

- 12 sizes available from 1.3 to 81 tonnes.
- Only 22 mm thick for easy insertion in tight spaces.
- SBR materials for high abrasion resistance and durability.
- Superposition of 2 lifting bags possible.
- Complies with EN 13731.

Accessories

- Scorp'Air S Inflation Kit