

# Road Rescue Combi MK



## Technical Information

Dimensions: L.960 x W.236 x H.223 mm

Opening Distance: 360 mm

Spread Force: 36 – 783 kN

Opening Width: 285 mm

Traction Width: 440 mm

Max Traction Force: 53 kN

Weight (including battery): 18.9 kg

Nominal Pressure: 700 bar

EN 13204 Class: CK36/360I-18.9

EN 13204 Cutting Power: 1I-2K-3J-4K-5J

NFPA Cutting Class: A7-B8-C7-D9-E8-F5

 **SCORPE**  
TECHNOLOGIES

### After Sales

sav@scorpe.eu

+33 (0)3 24 73 00 02

### Sales service

+33 (0)3 24 73 00 08

[www.scorpe.net](http://www.scorpe.net)

## Advantages

### DURABILITY and SAFETY

- Reinforced composite housing with impact protection cushions
- Removable waterproof cover for full battery protection
- Forged steel blades for improved cutting performance and increased durability
- 4 LED lights to illuminate the cutting area
- Remote control handle separated from the on/off switch for optimal safety

### ERGONOMICS and AUTONOMY

- Compact, lightweight, and well-balanced
- Compatible with the M18 battery (or with an adapter for the M28, as well as with any other commercially available battery)
- Same battery for all tools
- Battery available at all Milwaukee dealers

### USER-FRIENDLINESS

- Intuitive on/off switch with integrated lighting
- Asymmetrical control handle for easier recognition of the cutting direction
- Easy and fast battery insertion and replacement
- 360° fixed handle for quick use in any position

#### After Sales

#### Sales service