

Road Rescue Combi SK



Technical Information

DIMENSIONS: L.804 x l.236 x h.223 mm

SPREADING DISTANCE: 270 mm

SPREADING FORCE: 31-591kN

PULLING WIDTH: 395 mm

MAX SQUEEZING FORCE: 36 kN

WEIGHT (WITH BATTERY): 14,4 kg

NOMINAL PRESSURE: 700 Bar

CLASS EN 13204: BK31/270G-14,4

CUTTING POWER EN 13204: 1H-2G-3G-4H-5G

NFPA CUTTING CLASS: A6-B7-C6-D7-E7



After Sales

sav@scorpe.eu

+33 (0)3 24 73 00 02

Sales service

+33 (0)3 24 73 00 08

www.scorpe.net

Advantages

- THE ONLY combination tool on the market with CURVED BLADES
- THE LIGHTEST combined tool on the market

ROBUSTNESS AND SAFETY

- Reinforced composite casing with shock protection pads
- Removable waterproof cover for a complete protection of the battery
- Forged steel blades for better cutting performance and an extended resistance
- 4 LED lights to illuminate the cutting area
- Control handle far away from the On/Off switch for an optimal security

ERGONOMIC AND AUTONOMOUS

- Compact, light and balance
- Compatible with M18 battery (or with an adapter for M28 as well as any other commercially available battery)
- Same battery on all tools
- Battery available at all Milwaukee dealer

EASE OF USE

- Intuitive ON/OFF switch with built in light
- Unsymmetrical control handle for an easier recognition of the cutting direction
- Easy and quick battery insertion and replacement
- 360° fixed handle for a quick use in any position