Road Rescue
Spreader MS – Waterproof

Technical Information

DIMENSIONS: L.912 x l.250 x h.222 mm
SPREADING DISTANCE: 610 mm
SPREADING FORCE: 44 – 857 kN
MAX PULLING FORCE: 68 kN
MAX SQUEEZING FORCE: 149 kN
TRACTION WIDTH: 465 mm
WEIGHT (BATTERY INCLUDED): 18,1 kg
NOMINAL PRESSURE: 700 bar
EN CLASS 13204: AS44/ 610-18,1

SCORPE TECHNOLOGIES

After Sales
sav@scorpe.eu
+33 (0)3 24 73 00 02

Sales service
+33 (0)3 24 73 00 08

www.scorpe.net

As part of the improvement of its products, Scorpe reserves the right to modify the specifications without prior notice. Non-contractual photo.

Advantages

ROBUSTNESS AND SAFETY

– Reinforced composite casing with shock protection pads

– Removable waterproof cover for a complete protection of the battery

– Strong arms equipped with carbides tips and rumble strips for an optimal grip

– 4 LED lights to illuminate the cutting area

– Control handle far away from the On/Off switch for an optimal security

ERGONOMIC AND AUTONOMOUS

– Compact, light and balance

– Compatible with M18 battery (or with an adapter for M28 as well as any other commercially available battery)

– Same battery on all tools

– Battery available at all Milwaukee dealer

EASE OF USE

– Intuitive ON/OFF switch with built in light

– Unsymmetrical control handle for an easier recognition of the cutting direction

– Easy and quick battery insertion and replacement

WATERPROOF

– IP67 rated: fully dust-tight and waterproof

– Can be submerged to a depth of 1 m for up to 30 min

– Stays operational in rain, flooded areas, mud or debris

– Simply rinses clean with water after use

Accessories

- M28™ Red Lithium Battery 5.0 Ah
- Battery Adapter M28™
- Charger M28™ 220V & 12/12V
- Chain Set for Spreader MS
- TRANSPORT BAG

SCORPE TECHNOLOGIES

After Sales
sav@scorpe.eu
+33 (0)3 24 73 00 02

Sales service
+33 (0)3 24 73 00 08

www.scorpe.net

As part of the improvement of its products, Scorpe reserves the right to modify the specifications without prior notice. Non-contractual photo.