

# Road Rescue Spreader MS



## Technical Information

DIMENSIONS: L.912 x l.250 x h.222 mm

SPREADING DISTANCE: 610 mm

SPREADING FORCE: 44 – 857 kN

MAX PULLING FORCE: 68 kN

MAX SQUEEZING FORCE: 149 kN

TRACTION WIDTH: 465 mm

WEIGHT (BATTERY INCLUDED): 18,1 kg

NOMINAL PRESSURE: 700 bar

EN CLASS 13204: AS44/ 610-18,1

## Advantages

### ROBUSTNESS and SAFETY

- Reinforced composite casing with shock protection pads
- Removable waterproof cover for a complete protection of the battery
- Strong arms equipped with carbides tips and rumble strips for an optimal grip
- 4 LED lights to illuminate the cutting area
- Control handle far away from the On/Off switch for an optimal security

### ERGONOMIC and AUTONOMOUS

- Compact, light and balance
  - Compatible with M18 battery (or with an adapter for M28 as well as any other commercially available battery)
  - Same battery on all tools
  - Battery available at all Milwaukee dealer
- ### EASE OF USE
- Intuitive ON/OFF switch with built in light
  - Unsymmetrical control handle for an easier recognition of the cutting direction
  - Easy and quick battery insertion and replacement

#### After Sales

sav@scorpe.eu  
+33 (0)3 24 73 00 02

#### Sales service

+33 (0)3 24 73 00 08

[www.scorpe.net](http://www.scorpe.net)